



Migration from EN25B16 to EN25F16

Part No. :	EN25F16
Issued date :	2008 / 05 / 21
Prepared by :	FAE engineer <u>Sunny Tai</u>
Approval by :	FAE Manager <u>Jason Tseng</u>



1. Purpose

EN25B16 will EOL and be replaced by EN25F16 which can offer uniform 4Kbytes sector and allow for greater flexibility in applications. This note highlights the difference between those two devices. It helps customers to migrate into new device.

2. Difference

- **High Performance**

EN25F16---100MHz clock rate

EN25B16---75MHz clock rate

- **Block Sector Architecture**

EN25F16 : Uniform sector Architecture

- 512 sectors of 4KB
- 32 blocks of 64KB
- Any sector or block can be erased individually

EN25B16 : Flexible sector Architecture

- Two 4KB, one 8KB, one 16KB, one 32KB and thirty one 64KB sectors

- **Erasable**

EN25F16--- Sector, Block or Chip erasable

EN25B16--- Sector or Chip erasable

Note : In the condition of erasing the boot sector of EN25B16 to be replaced with EN25F16, one or multiple sector erase command (20h) must be issued in EN25F16 depending on the sector size. The correlation table is shown below.



Sector Size	Address Range	EN25B16	EN25F16
4KByte	00000h-00FFFh	Issue sector erase (D8h) for sector 0	Issue sector erase (20h) for sector 0
4KByte	01000h-01FFFh	Issue sector erase (D8h) for sector 1	Issue sector erase (20h) for sector 1
8KByte	02000h-03FFFh	Issue sector erase (D8h) for sector 2	Issue sector erase (20h) for sector 2
			Issue sector erase (20h) for sector 3
16KByte	04000h-07FFFh	Issue sector erase (D8h) for sector 3	Issue sector erase (20h) for sector 4
			Issue sector erase (20h) for sector 5
			Issue sector erase (20h) for sector 6
			Issue sector erase (20h) for sector 7
32KByte	08000h-0FFFFh	Issue sector erase (D8h) for sector 4	Issue sector erase (20h) for sector 8
			.
			.
			Issue sector erase (20h) for sector 15

- **Support Lockable 512 byte OTP security sector**
EN25F16---Yes
EN25B16---No

● **Manufacturer and Device Identification**

EN25F16 :

OP Code	(M7-M0)	(ID15-ID0)	(ID7-ID0)
ABh			14h
90h	1Ch		14h
9Fh	1Ch	3115h	

EN25B16 :

Boot Type	OP Code	(M7-M0)	(ID15-ID0)	(ID7-ID0)
EN25B16(Bottom Boot)	ABh			34h
	90h	1Ch		34h
	9Fh	1Ch	2015h	
EN25B16T(Top Boot)	ABh			44h
	90h	1Ch		44h
	9Fh	1Ch	2015h	

● **Protected Area Sizes Sector Organization**

EN25F16 :

Status Register Content			Memory Content			
BP2 Bit	BP1 Bit	BP0 Bit	Protect Blocks	Addresses	Density(KB)	Portion
1	1	1	All	000000h-1FFFFFFh	2048KB	All
1	1	0	All	000000h-1FFFFFFh	2048KB	All
1	0	1	16 to 31	100000h-1FFFFFFh	1024KB	Upper 1/2
1	0	0	24 to 31	180000h-1FFFFFFh	512KB	Upper 1/4
0	1	1	28 to 31	1C0000h-1FFFFFFh	256KB	Upper 1/8
0	1	0	30 to 31	1E0000h-1FFFFFFh	128KB	Upper 1/16
0	0	1	31	1F0000h-1FFFFFFh	64KB	Upper 1/32
0	0	0	None	None	None	None

EN25B16 :

Status Register Content			Memory Content			
BP2 Bit	BP1 Bit	BP0 Bit	Protect Sectors	Addresses	Density(KB)	Portion
1	1	1	All	000000h-1FFFFFFh	2048KB	All
1	1	0	Sector 0 to 19	000000h-0FFFFFFh	1024KB	Lower 1/2
1	0	1	Sector 0 to 4	000000h-00FFFFh	64KB	Lower 1/32
1	0	0	Sector 0 to 3	000000h-007FFFh	32KB	Lower 1/64
0	1	1	Sector 0 to 2	000000h-003FFFh	16KB	Lower 1/128
0	1	0	Sector 0 to 1	000000h-001FFFh	8KB	Lower 1/256
0	0	1	Sector 0	000000h-000FFFh	4KB	Lower 1/512
0	0	0	None	None	None	None

● Instruction Set Comparison

A Sector Erase (20h) instruction is implemented in EN25F16 for 4KB sector erase. A Block Erase (D8h) instruction in EN25F16 is compatible with EN25B16 for 64KB block erase and the chip erase instruction is same between two devices.

EN25F16 :

Instruction Name	Byte 1 Code	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	n-Bytes
Sector Erase	20h	A23-A16	A15-A8	A7-A0			
Block Erase	D8h/ 52h	A23-A16	A15-A8	A7-A0			
Chip Erase	C7h/ 60h						
Enter OTP mode	3Ah						

EN25B16 :

Instruction Name	Byte 1 Code	Byte 2	Byte 3	Byte 4	Byte 5	Byte 6	n-Bytes
Sector Erase	D8h	A23-A16	A15-A8	A7-A0			
Bulk Erase	C7h						



Revisions History

Revision No	Description	Date
A	Initial Release.	2008/05/21